

# Quality Specification van Clewe Sun Protection GmbH

Subject: 2008 – Jaspé  
 Version: pleated blind  
 Date: 07/2023



## Standard:

## Tolerance:

### Fabric characteristics:

|                   |                     |         |
|-------------------|---------------------|---------|
| Fabric width:     | 230cm               | +/- 5%  |
| Fabric weight:    | 150g/m <sup>2</sup> | +/- 10% |
| Fabric thickness: | 0,30mm              | +/- 10% |
| Pleat height:     | 20mm                | +/- 1mm |

### Technical parameters:

|                            |  |
|----------------------------|--|
| Colour:                    | According to master samples approved by van Clewe. Optical colour inspection decisive, if necessary, validation by colour measurement under D65 daylight, colour measurement with CMC 2:1, permissible Delta E +/- 1.5 |
| Flame retardancy:          | B1 – DIN 4102, NFPA 701  |
| Light fastness: *1         | 6-7  |
| Rubbing fastness (dry): *2 | ≥3   |
| Dimensional stability: *3  | lengthwise and crosswise max. -1%  |
| Bow and skew:              | max. 2% of the delivered fabric width  |

### Defects:

|                            |  |
|----------------------------|--|
| Definition of faults:      | Any deviation in product and/or structure regarding to the master sample visible from 1 meter distance.  |
| Defects marking:           | <u>Point fault</u> is marked with tapes on the position of the fault.<br><u>Length fault</u> is also marked on the position of the fault with a double tape- once at beginning and once at the end.    |
| Point fault compensation:  | point faults are compensated by 0,1mtr. full width   |
| Length fault compensation: | length faults are compensated in full length and width   |
| Admissible faults rate:    | max. 3 per 10 meters   |
| Cuts:                      | max. 1 joint   |
| Complaints/ Rejects:       | A batch number and a proof of the faults (pictures or samples) are essential for traceability and noticing the source. Material characteristics or unavoidable variations are no reason for rejection. |

### Packaging and make up:

|                        |  |         |
|------------------------|--|---------|
| Packaging units:       | 50m <sup>2</sup>   | +/- 10% |
| Packaging:             | packed in boxes  |         |
| Packaging material:    | wood and cardboard   |         |
| Labeling:              | article and colour -name and -number, batch number, meter (net & gross), -one label on the side of the box and one on the box- |         |
| Customs tariff number: | 59039099   |         |

\*1 ISO 105-B02, \*2 DIN EN ISO 105-X12, \*3 DIN EN ISO 3759